

EX2SC

EN857 2SC



-size	DN	"	"	mm	PSI	MPa	PSI	MPa	mm	m	kg/100m	REF.
-4	6	1/4	0,54	13,7	5800	40,0	23200	160,0	75	1650	28	4EX2SC
-5	8	5/16	0,59	15,1	5075	35,0	20300	140,0	85	1500	34	5EX2SC
-6	10	3/8	0,69	17,5	4775	33,0	19125	132,0	90	1000	41	6EX2SC
-8	12	1/2	0,83	21,0	3975	27,5	15950	110,0	130	750	56	8EX2SC
-10	16	5/8	0,94	24,0	3625	25,0	14500	100,0	170	550	64	10EX2SC
-12	19	3/4	1,09	27,8	3100	21,5	12450	86,0	200	450	81	12EX2SC
-16	25	1	1,41	35,7	2375	16,5	9550	66,0	250	275	125	16EX2SC

**RECOMMENDED FOR** High pressure hydraulic application. Easy to route and install in tight areas.

**TUBE** NBR (nitrile) based.

**REINFORCEMENT** Two braids of high tensile steel wire.

**COVER** SBR (Styrene-Butadiene Rubber) based.

**TEMPERATURE RANGE** Hydraulic fluids : -40 to +100°C ; water based fluids : -40 to +70°C ;  
water : 0 to +70°C.

**STANDARDS** EN 857 2SC. ISO 11237 2SC.

**COUPLINGS** EX

**PACKAGING** Min. length of 3 meter, +/- 10% tolerance on total pack quantity  
Hose will be stacked on pallets in bales, stretch wrapped and banded.