


STAUFF Form Adaptor Ring Type FI-AR ■ Series L / S



Ordering Codes

FI-AR-10*L*-V*-W3

* STAUFF Form Ring
with Integrated Elastomeric Sealing

FI-AR

* Outside Tube Diameter D1 (in mm)

-10

* Series Light Series
 Heavy Series

L

S

* Seal Material FKM (Viton®)

-V

* Material Code Steel, zinc/nickel-plated

-W3

Please contact STAUFF for alternative
materials and surface finishings.

Series	Tube OD (mm/in)	PN (bar/psi)	Dimensions (mm/in)		Weight (kg/lbs) ca. per 100 ²	Ordering Codes
	D1		D2	L1		
L	6	500	10,2	5,3	0,09	FI-AR-06L/S-V-W3
	.24	7250	.40	.21	.20	
	8	500	12,2	5,3	0,1	FI-AR-08L/S-V-W3
	.31	7250	.48	.21	.22	
	10	500	14,2	5,9	0,17	FI-AR-10L/S-V-W3
	.39	7250	.56	.23	.37	
	12	400	16,2	5,9	0,19	FI-AR-12L/S-V-W3
	.47	5800	.64	.23	.42	
	15	400	20,2	5,3	0,23	FI-AR-15L-V-W3
	.59	5800	.80	.21	.51	
	18	400	24,2	5	0,29	FI-AR-18L-V-W3
	.71	5800	.95	.20	.64	
	22	250	27,2	6	0,42	FI-AR-22L-V-W3
	.87	3625	1.07	.24	.92	
	28	250	33,2	6	0,52	FI-AR-28L-V-W3
	1.10	3625	1.31	.24	1.14	
	35	250	42,2	6,3	0,94	FI-AR-35L-V-W3
	1.38	3625	1.66	.25	2.07	
	42	250	49,5	8	1,09	FI-AR-42L-V-W3
	1.65	3625	1.95	.31	2.40	
S	6	800	10,2	5,3	0,09	FI-AR-06L/S-V-W3
	.24	11600	.40	.21	.20	
	8	800	12,2	5,3	0,1	FI-AR-08L/S-V-W3
	.31	11600	.48	.21	.22	
	10	800	14,2	5,9	0,17	FI-AR-10L/S-V-W3
	.39	11600	.56	.23	.37	
	12	630	16,2	5,9	0,19	FI-AR-12L/S-V-W3
	.47	9135	.64	.23	.42	
	16	630	22,2	5	0,26	FI-AR-16S-V-W3
	.63	9135	.87	.20	.57	
	20	400	27,2	5,2	0,42	FI-AR-20S-V-W3
	.79	5800	1.07	.20	.92	
	25	400	33,2	6	0,69	FI-AR-25S-V-W3
	.98	5800	1.31	.24	1.52	
	30	400	37,2	6,3	0,79	FI-AR-30S-V-W3
	1.18	5800	1.46	.25	1.74	
	38	400	49,5	8	1,79	FI-AR-38S-V-W3
	1.50	5800	1.95	.31	3.94	

Standard seal material is FKM (Viton®).