

CLEAN MASTER™ PRESSURE WASH - 2 WB

FORMERLY POWERCLEAN



| ↔ | | ○ | | ⌚ | | 🔥 | | 🔧 | | 📦 | | 📏 | |
|-------|----|------|------|------|------|------|-------|-------|----|----|---------|--------------------|--|
| -size | DN | " | " | mm | PSI | MPa | PSI | MPa | mm | m | kg/100m | REF. | |
| -5 | 8 | 5/16 | 0,63 | 16,0 | 6000 | 42,0 | 18000 | 124,0 | 55 | 91 | 38 | CLEAN MAS 5PW6000B | |
| -6 | 10 | 3/8 | 0,74 | 18,7 | 6000 | 42,0 | 18000 | 124,0 | 65 | 91 | 52 | CLEAN MAS 6PW6000B | |
| -8 | 12 | 1/2 | 0,86 | 21,7 | 5000 | 35,0 | 15000 | 103,0 | 90 | 91 | 63 | CLEAN MAS 8PW5000B | |
| -8 | 12 | 1/2 | 0,86 | 21,7 | 5000 | 35,0 | 15000 | 103,0 | 90 | 91 | 63 | CLEAN MAS 8PW5000 | |

RECOMMENDED FOR

Use on pressure cleaning equipment for commercial and industrial purposes, in food processing, sanitation and car wash applications.
All hot and cold water high-pressure cleaning services.

TUBE

NBR (Nitrile) based. Black.

REINFORCEMENT

Two braids of high tensile steel wire

COVER

Modified Nitrile. MSHA approved. Available in black, blue (B) and grey (G). Blue and grey covers are non-marking.

TEMPERATURE RANGE

-40°C to +121°C and +150°C intermittent (to EN 1829-2).
For water emulsions, etc. see Temperature Limits Table.

STANDARDS

Exceeds EN 1829-2.

COUPLINGS

MegaCrimp®.

CHARACTERISTICS/BENEFITS

Abrasion and ozone resistant cover.

IMPORTANT

Not for steam service.