


PTFE**PTFE HOGEDRUKSLANG MET RVS BUITENMANTEL**

KG-2010

Temp.bereik: -70°C / +260°C


Persmantel: **PM 6.****Buitenmantel = RVS 304.**

Slang Ø inw.(mm)	Slang Ø uitw.(mm)	Werdruk (Bar *)	Barstdruk (Bar *)	Buig- radius	Gew. (gr/mtr)	Bestel nr.
6,4 (1/4")	9,0	175	700	45	87	PTFENW6
8,0 (5/16")	10,8	150	600	50	127	PTFENW8
9,5 (3/8")	12,4	135	540	55	145	PTFENW10
12,7 (1/2")	15,7	120	480	70	212	PTFENW13
16,0 (5/8")	19,1	100	400	130	260	PTFENW16
19,0 (3/4")	22,2	90	360	190	321	PTFENW20
25,4 (1")	29,3	65	260	270	450	PTFENW25

LET OP: *Drukken gelden bij een bedrijfstemperatuur van +20°C !!**PTFE/G****PTFE HOGEDRUKSLANG MET RVS BUITENMANTEL**

KG-2010

Temp.bereik: -70°C / +260°C

Persmantel: **PM 7.****Buitenmantel = RVS 304.**

Slang Ø inw.(mm)	Slang Ø uitw.(mm)	Werdruk (Bar *)	Barstdruk (Bar *)	Buig- radius	Bestel nr.
6,4 (1/4")	12,7	130	520	20	PTFEGNW6
9,5 (3/8")	16,2	120	480	30	PTFEGNW10
12,7 (1/2")	19,7	110	440	40	PTFEGNW13
16,0 (5/8")	22,9	80	320	50	PTFEGNW16
19,0 (3/4")	27,5	70	280	80	PTFEGNW20
25,4 (1")	34,3	50	200	100	PTFEGNW25
31,8 (1-1/4")	42,0	45	180	120	PTFEGNW32
38,1 (1-1/2")	49,2	40	160	140	PTFEGNW40
50,8 (2")	63,6	35	140	175	PTFEG NW50

LET OP: *Drukken gelden bij een bedrijfstemperatuur van +20°C !!